

owa11A

Tracking and Telemetry platform

The owa11A platform is an optimized, fully featured, vehicle, asset tracking and telemetry unit. Its design has been the result of the experience of Owasys with over 100.000 units on field during last 12 years. The owa11A is an ideal product for a wide range of applications as Transport & Logistics, Security & Surveillance, Trailer Tracking, Insurance Rental, Caravans, etc....

Full-featured asset and vehicle tracking platform

- **Fully configurable** functionality.
- **OTA update** capability for configuration and firmware.
- Quad band GSM/GPRS (**integrated antennas**).
- Optional **HSPA+** module.
- **Cell ID** information provided.
- Nominal Range from 6 to 30V DC.
- Three power modes.
- **High Capacity 1800 mAh integrated back-up battery.**
- Internal **3-axis accelerometer**.
- 2 I/Os each configurable as:
 - Digital Inputs
 - Digital Outputs open collector 100mA*
 - Analog Inputs, 2 Ranges 0-5V or 0-30V
- *Factory option in I/O-0 for High side output 1A.
- Waterproof housing **IP67**.
- **CE certified/ ROHS**.
- Fully designed and manufactured in EU.

The **owa11A** has been designed in a compact size with **GPS (GLONASS)** and **GPRS** internal antennas focussed to simplify the installation. The large 1800 mAh battery combined with the different sleep modes provide the customer with a long time period of reporting on battery power.



Improved M2M communication technology

MQTT based: lightweight publish/subscribe messaging protocol well suited to work in the mobile environment.

MQTT features:

- fast response and throughput.
- low battery and bandwidth usage.

MQTT is a perfect fit for use cases where:

- connectivity is intermittent.
- bandwidth is at a premium.
- an enterprise application needs to interact with one or more devices.
- devices need to send data fast and reliably without requiring code retry logic.

MQTT allows the deployment of devices to all environments, private and NAT-ed networks.

owasys
Advanced Wireless Devices

TECHNICAL SPECIFICATIONS

❖ Interfaces

- Two I/Os each configurable as:
 - a. Digital Input (Maximum input voltage 50V)
LOW = 0 - 2.5V
HIGH = 5 - 50V
 - b. Digital Output open collector 100mA *
 - c. Analog Input, 2 Ranges 0-5V or 0-30V
*Factory option in IO1 for High side output 1A.
- SIM Slot
- GSM / GPRS with internal antenna
- GPS with internal antenna
- 1 bi-colour Status LED
- Movement Sensor

*NOTE: Optional

❖ Power Supply

- Nominal Range: 6 V a 30 V.
- Typical current consumption @ 12v:

Off: Acc + Inputs	670 uA
STANDBY: GSM + Acc + Inputs	3,8 mA
RUN: GPRS + GPS + Acc + I/Os	42 mA

Wakeup reasons	
Off:	Accelerometer, power fail, digital inputs, RTC
STANDBY:	Accelerometer, power fail, digital inputs, GSM (call or SMS), RTC

❖ Battery

- Back Up Battery Li-Ion 3.7V 1800 mAh.

❖ Temperature

Operation Temperature	-20°C to +60°C
Battery Charge	0°C to 45°C
Storage Temperature** (1 month)	-5°C to +35°C
Storage Temperature** (3 months)	0°C to +35°C

** NOTE: Storage Temperature limited because of Li-Ion battery.
After 3 months, battery should be charged to 40-50% of capacity and stored at ambient temperature 25± 5°C, 65±20% RH for 12 months.
After 12 months a complete charge/discharge cycle should be carried out.

❖ GSM/GPRS

- GSM850 + EGSM900 + GSM1800 + GSM1900
- Class 4 (2W) GSM850/EGSM900
- Class 1 (1W) GSM1800/GSM1900
- GPRS Class B, Class 10 (4+2)
- SMS (MT/MO)
- Supports multiplexed communication, allowing GSM and SMS events during GPRS sessions

NOTE: Optional HSPA+ Module

❖ GPS

- 56-channels
- GLONASS (Optional)
- SBAS: WAAS, EGNOS, MSAS
- Precision: 2.5 meters CEP
- Signal Acquisition:
 - Cold Start: 29 sec
 - Aided Start: 5 sec
 - Readquisition: 1 sec

❖ Mechanics

- Plastic
- Dimensions: 101x61x30 mm
- Weight: 190 gr
- Power Supply Cable+ I/O*
- Fixation with adhesive

